



## TWO POWERFUL OPTIONS FOR AN END-TO-END CLEAN.

Featuring patented V-Flex® technology and exclusive 4-wheel drive capability, AquaNaut® suction cleaners are the first of their kind to clean corner to corner without clogging or getting stuck. They expertly navigate any surface while maintaining optimal suction, even when encountering tough obstacles and large debris. Plus, with two dependable options, there's a perfect solution for every pool.



**AQUANAUT 250** Everything you need and nothing you don't.



**AQUANAUT 450**More wheels to cover even more ground.

EXPERT LINE
ONLY FROM POOL PROS



# Unrivaled performance. Unstoppable results.



## 4-WHEEL DRIVE CAPABILITY (450 ONLY)

Exclusive 4-wheel drive offers superior power, traction and stability for end-to-end cleaning in pools of all kinds.



## EXPERTLY NAVIGATES ANY POOL SURFACE

Rugged tire treads provide superior climbing power and maneuverability on surfaces like concrete, gunite, vinyl, fiberglass, tile and pebble.



## IDEAL FOR USE WITH VARIABLE-SPEED PUMPS

V-Flex technology ensures optimal suction at any flow, making AquaNaut the perfect partner for variable-speed pumps.



**V-FLEX TECHNOLOGY** features patented self-adjusting variable vanes that maximize power while virtually eliminating clogs, creating constant suction power—even at lower flow—and ensuring a complete clean every time.



## Three easily interchangeable

**throats** improve suction performance and allow larger debris to pass



Multiple pre-programmed steering sequences ensure endto-end coverage, including walls

#### Advanced design

optimizes flow performance for use with variable-speed pumps

> Patented adjustable roller skirt never loses suction on uneven surfaces



## **SPECIFICATIONS** FEATURE AQUANAUT° 250 AQUANAUT° 450 PBS22CST PBS42CST Part Number Model Type 2-wheel drive 4-wheel drive Up to 20' x 40' and pools Pool Size Up to 16' x 32' with deep ends 40' Hose Length 33' Concrete, gunite, vinyl, Concrete, gunite, vinyl, Pool Surface fiberglass, tile, pebble\* fiberglass, tile, pebble\* Minimum Pump 0.5 HP or 35 GPM 0.5 HP or 35 GPM Size/Flow Rate Drive Sequence Turns every 8' to 10' Turns every 11' to 14'

## THROAT OPTIONS (INCLUDED WITH ALL MODELS)



#### Small throat

For better suction
 with lower flow rate
 and smaller pump
 Can use with
 variable-speed pump
 at lower speeds



#### Medium throat

» Use for almost all average filtration systems and installations



#### Large throat

» For better suction
 with higher flow rate
 and larger pump
 » Can use with
 variable-speed pump
 at higher speeds

\*Optional tape tires may be required for smoother surfaces.

» hayward.com » 1-888-HAYWARD

Pumps » Filters » Heaters » Cleaners » Sanitization » Automation » Lighting » Water Features » White Goods

