

## **SUPER II™ PUMP**

MAX-RATED, HIGH-PERFORMANCE PUMP SERIES



# Performance of a lifetime.

Power your system with the max-rated, highperformance Super II pump series from Hayward. These efficient, large-capacity pumps are built to last and engineered to perform even under the most demanding conditions.

Convenient features include a see-through cover so pool owners know exactly when to empty the extra-large debris basket. Performance features include full-flow hydraulics that allow greater flow at a lower cost of operation and a housing design that makes it as quiet as it is dependable.

Super II Pumps. The superior choice.

All Components Molded of Corrosion-Proof Reinforced Thermoplastic

for extra durability and long life.

#### See-Through Strainer Cover

lets you see when basket needs cleaning and eliminates guesswork. Test feature allows line pressure test to 40 psi (2.75 bar).

#### Rugged, One-Piece Housing

with full-flow ports, ensures rapid priming and continuous operation.

#### Corrosion-Proof Impeller

provides high-volume output to accommodate even the most demanding installations, including pool/spa combinations and in-floor cleaning systems.



Heat-Resistant, Industrial -Size Ceramic Seal

is long-wearing. For fresh or saltwater use.

#### Heavy-Duty, High-Performance Motor

with airflow ventilation for quieter, cooler operation.

#### Uni-Bracket Mounting Base

provides stable, stress-free support, plus versatility for any installation requirement. Adapts 48- and 56-frame motors.

#### Service-Ease Design

allows simple access to all internal parts. Motor and entire drive group assembly can be removed, without disturbing pipe or mounting connections, by disengaging just six bolts.

	OVERAL	L DIMENSI	ONS	
· A*	+	9-3/8* (238 mm)	<del> </del>  -	9-3/8" (238 mm)
			12-3/16" (310mm) 8-3/16" (208 mm)	
			1 4	7-5/8*

MODEL	Motor Power			Pipe Size	Dimension "A"	
	Total HP	Rated HP	Service Factor	inches	inches	mm
Max Rated 220V/50Hz 1	PH					
SP3007X1051	1.10	1	1.10	1 ½	14 ½	368
SP3010X1551	1.50	1 ½	1.00	2	15 %	397
SP3015X2051	2.00	2	1.00	2	16 %	422
SP3025X30G51	3.00	3	1.00	2	17 3/4	451
Max Rated 220-240/3	80-415/50	Hz 3PH				
SP303053	3.00	3	1.00	2	17 ½	445

#### m ft. 27 90 24 80 21 70 18 60 **TOTAL HEAD** 15 50 12 40 9 30 SP3025X30G51 SP303053 6 20 SP3015X2051 3 10 SP3010X1551 SP3007X1051 0

80

303

CAPACITY PER MINUTE

100

SUPER II PUMP FLOW VS. TOTAL HEAD

To take a closer look at Hayward Pumps, go to www.haywardpool.com



120

455

140

531

160 **GPM** 

606 LPM





### Super II 155-Cubic-Inch (2500cc) Basket

is more like a bucket. The Super II Pump Series features impressive leaf-holding capacity. Rigid construction includes loadextender ribbing for free-flowing operation, even under extra-heavy debris loads.

Super II Pump Series pumps are listed by:



20

76

0

40

151

60

227